

HMK® P23

Polish Preserver

“No Rinse“

Self-shining care emulsion to refresh worn and dulled natural and artificial stone surfaces.

Solvent free.

No need to buff after application.



HMK® P23 is a concentrated acrylic care emulsion that refreshes worn and dulled natural and artificial stone surfaces. A brilliant silky shine is developed without the need for polishing. The protective film developed with regular use increases water and dirt resistance and makes textured and rough surfaces easier to clean. For internal use only.

Instructions: Ensure that underfloor heating is switched off and the surface is cool. Clean the surface thoroughly and let it dry (max residual moisture of 2-4%). Shake well before use. For first time application, dilute P23 1:10 with clean water and apply thinly and evenly using a clean non-fraying cloth, sponge or washmop. For very absorbent surfaces, use a more concentrated mixture.

For regular maintenance occasionally add 100-200ml of HMK P23 for every 10 litres of wash water and mop 5 to 10m² at a time wringing the mop frequently in same bucket of solution. Do not re-mop or rinse areas once cleaned. Replace the solution when it becomes dirty. High traffic areas may require more frequent treatments and a more concentrated mixture.

Important: Do not walk on the treated area until dry, about 50-60 minutes.

Buff to a higher shine using a regular floor machine (900-1500 rpm) with a white, tan or red polyester pad.

Use HMK® P24 Liquid Stone Soap -no rinse- for daily cleaning alternated with HMK® P23 as required.

Use HMK® R55 Intensive Cleaner -acid free- to clean surface thoroughly before first application and to periodically remove the P23 film and refresh the surface.

Coverage: About 150-250m² per litre.

Warning: Chemical product. Keep out of the reach of children and safe from frost.

Packaging: 12 x 1 litre bottles/box; 4 x 5 litre cans/box; 2 x 10 litre cans/box.

Storage: Store in a cool place. Do not allow to freeze.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12 and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stonecare for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stonecare shall not be liable for any consequential damages. No other warranty or representation is made or implied.