

# HMK® R55 Intensive Cleaner Acid Free

Especially suitable for polished marble and granite.

Removes dirt, calcium/soap scum deposits, grout residue, construction dirt and light wax coats.

For use on all surfaces and finishes.



HMK® R55 is a superior PH 8.5 neutral concentrated cleaner for removing general construction dirt, emulsion paint, wax coatings, the residual film built up from regular cleaning products as well as oil, grease and light cement film from all natural and artificial stone surfaces. R55 has been specially developed for use on polished and fine honed marble, limestone and travertine. For internal and external use.

**Instructions:** If under floor heating exists, switch it off and allow the surface to cool. Apply R55 diluted with water (1:2 to 1:10) depending on the intensity of the dirt. Use a scrubbing brush, stiff hand brush or suitable pad to work the R55 into the surface. Leave for around 10 minutes but do not allow to dry, scrub the area again and remove the dirty liquid. Afterwards rinse the area thoroughly with clean water. Repeat the procedure as necessary. For stubborn stains, R55 can be used undiluted. For periodic refreshing of surfaces and to remove protective films use R55 diluted about 1:20.

When using a wet vacuum we recommend that you add HMK® Z102 Defoamer to the water to regulate the amount of foam.

**Important:** Do not apply in direct sunlight. Do not apply on plastic, polished or waxed wood and lacquered areas. If these areas are splashed, remove splashes immediately and rinse thoroughly with clean water.

**Coverage:** About 5-15m<sup>2</sup> per litre undiluted and up to 150m<sup>2</sup> per litre for periodic cleaning.

**Warning:** Chemical product. Non-flammable, non-toxic, no fumes, mild odour. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information.

**Packaging:** 12 x 1 litre bottles/box; 4 x 5 litre cans/box; 2 x 10 litre cans/box.

**Storage:** Store in cool place.

**Testing:** Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12 and above 25°C.

**Limitation of liability:** The liability of HMK® Moeller Stonecare for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stonecare shall not be liable for any consequential damages. No other warranty or representation is made or implied.