

# HMK® R61

## Porcelain Tile Cleaner

### Alkaline Based

Removes oily and greasy deposits, general construction dirt and film built up from regular cleaning products.

For glazed, unglazed, polished, honed and textured effect porcelain.

**Concentrated.**



HMK® R61 is a special concentrated alkaline based cleaner that removes oily and greasy deposits, general construction dirt, light cement film and film built up from regular cleaning products from glazed, unglazed, polished, honed and natural effect porcelain. Polished surfaces will not be damaged. For internal and external use.

Recommended for cleaning prior to impregnation with HMK® S43 Porcelain Tile Impregnator and for periodic maintenance. HMK® R61 should not be used on other surfaces. Avoid contact with metal since fumes will cause etching.

**Note:** For removal of medium or heavy cement/grout residue, use HMK® R63 Concrete Film Remover.

**Instructions:** If under floor heating exists, switch it off and allow the surface to cool. Plants and all adjacent surfaces must be well protected from splashes. Apply R61 diluted with water (1:2 to 1:10) depending on the intensity of the dirt. Use a scrubbing brush, stiff hand brush or suitable pad to work R61 into the surface. Leave for around 10 minutes but do not allow to dry. Scrub the area again and remove the dirty liquid. Afterwards rinse the area thoroughly with clean water. For ingrained and stubborn dirt repeat the treatment.

When using a wet vacuum we recommend that you add HMK® Z102 Defoamer to the water to regulate the amount of foam.

**Coverage:** About 10-20m<sup>2</sup> in strong solution and 40-80m<sup>2</sup>/litre for periodic cleaning.

**Warning:** Chemical product. Contains sodium hydroxide. Corrosive. Avoid eye/skin contact. If exposed, wash/flush with water. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information.

**Packaging:** 12 x 1 litre bottles/box; 4 x 5 litre cans/box; 2 x 10 litre cans/box.

**Storage:** Store in a cool place. Keep lid tightly closed.

**Testing:** Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12 and above 25°C.

**Limitation of liability:** The liability of HMK® Moeller Stonecare for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stonecare shall not be liable for any consequential damages. No other warranty or representation is made or implied.