

HMK® R63 Concrete Film Remover

Removes grout and cement residue, heavy construction dirt, limescale, calcium deposits and efflorescence.

Acid based.

FOR PROFESSIONAL USE ONLY!



HMK® R63 is a strong acid based concentrated cleaner for removing cement and mortar residue, limescale, calcium deposits and heavy duty construction dirt from all acid tolerant natural and artificial stone, ceramic tiles, porcelain and rough concrete surfaces. Not for use on polished surfaces. Suitable for internal and external use.

Note: Use the milder HMK® R69 Exterior Stone Cleaner if acid fumes are a concern. Do not apply in direct sunlight. Acid-sensitive surfaces such as polished and honed marble, limestone, agglomerates and concrete products, plastics and certain metal surfaces can be damaged by contact with R63. R63 is not suitable for latex/resin modified grouts; consider using HMK® R99 Stripper-Thinners as an alternative.

Instructions: Protect all adjacent surfaces. If under-floor heating exists, switch it off and allow the surface to cool. Dilute R63 with clean water (1:4 to 1:20) depending on the level of contamination. Wet the surface and apply with a scrubbing brush, stiff brush or a suitable pad. Leave for a short time to work but do not allow to dry. Scrub the area again and remove the dirty liquid. Afterwards clean the area thoroughly using HMK® R55 Intensive Cleaner -acid free- diluted with clean water (about 1:20) and remove the dirty liquid. Afterwards rinse the area thoroughly with clean water. Repeat the procedure in the case of very strong contamination.

When using a wet vacuum we recommend that you add HMK® Z102 Defoamer to the water to regulate the amount of foam.

Coverage: About 5-50m² depending on rate of dilution and level of contamination.

Warning: Contains Inhibited dilute hydrochloric acid. Corrosive. Fumes may cause eye and skin burns and oxidation. Avoid eye/skin contact. If exposed, wash/flush with water and seek medical attention. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information.

Packaging: 12 x 1 litre bottles/box; 4 x 5 litre cans/box; 2 x 10 litre cans/box.

Storage: Store in a cool place. Keep lid tightly closed.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12 and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stonecare for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stonecare shall not be liable for any consequential damages. No other warranty or representation is made or implied.