

HMK® S32

Stain Protection

Water Based



Superior oil, water, and grease protection.

For all natural and artificial stone, terracotta, clay tiles and brick/block paving.

Environmentally friendly and odourless.

HMK® S32w is a solvent free impregnator that reduces the penetration of oil, water and dirt on soft and hard natural and artificial stone surfaces, agglomerates, concrete block, terracotta, brick and block paving, clay surfaces and unglazed tiles. Especially good for use on highly absorbent honed and textured surfaces. Surfaces remain vapour permeable. For internal and external use.

Since S32w is solvent free buildings can remain occupied during the application process. Colour and texture will not be affected.

Instructions: If under floor heating exists, switch it off and allow the surface to cool. Clean surface thoroughly and allow it to dry (max. residual moisture of 4-6%). Shake well before use as the active ingredients settle during storage. Apply treatment generously and evenly with a soft paintbrush, roller with short fibres or HMK® Z170 & HMK® Z171 Application Brushes. Further coats can be applied after an hour or two but only with a brush. If using a roller you must allow 12 to 24 hours as it will draw out earlier coats. Repeat treatment for very absorbent surfaces after 12 to 24 hours. For less absorbent stone surfaces, remove excess with a paper towel before it dries. The treatment can leave a residual film. Remove this film after around 12 hours with clear water (do not use any cleaning products) and a wash mop.

Important: Do not walk on the treated area until dry, about 8 to 12 hours.

Once dry the residual material is not harmful and complies with food hygiene standards.

To clean surface thoroughly before treatment use HMK® R55 Intensive Cleaner -acid free.

For regular cleaning and continued protection use HMK® P24 Liquid Stone Soap, a no-rinse natural product.

Coverage: About 5-20m²/litre depending on the nature of the surface.

Warning: Chemical product. Avoid ingesting and eye/skin contact. If ingested, do not induce vomiting; give plenty of water and call physician immediately. If eye contact occurs, flush with plenty of water. If skin contact occurs, wash with soap and water. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information.

Packaging: 12 x 1 litre bottles/box; 4 x 5 litre cans/box; 2 x 10 litre cans/box.

Storage: Store in cool place. Keep lid tightly closed.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12 and above 25 °C.

Limitation of liability: The liability of HMK® Moeller Stonecare for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stonecare shall not be liable for any consequential damages. No other warranty or representation is made or implied.