

# HMK® S44

## Colour Enhancer

### Extra

**Superior oil and grease protection for all finishes on natural and artificial stone surfaces.**

**Smear free application.**

**Fast acting protection.**

HMK® S44 is a fast acting special colour enhancing impregnator for all natural and artificial stone, agglomerates and terrazzo. S44 can be applied quickly with only a minimal risk of smearing and reduces the penetration of water, dirt, oil and grease on all finishes, including polished surfaces. Surfaces remain vapour permeable. For internal and external use. The colour and structure of the surface will be significantly enhanced.

**Instructions:** If under floor heating exists, switch it off and allow the surface to cool. Clean stone surface thoroughly and allow it to dry (max residual moisture of 2-4%). Apply S44 generously and evenly using a clean soft paintbrush, roller with short fibres or HMK® Z170 & HMK® Z171 Application Brushes. Remove excess product before drying on the surface. Repeat treatment for very absorbent surfaces after 12 hours. For less absorbent stone surfaces, remove excess with a paper towel before it dries.

If applied to walls, HMK® S44 can be sprayed onto the surface. A suitable face mask must be worn to protect against inhalation of vapours.

**Important:** Do not walk on the treated surface for 2 to 4 hours after treatment is completed. Protect surface from rain and humidity for 12 hours. Do not apply to rubber, plastics, lacquered or varnished surfaces and solvent intolerant materials. Remove all foodstuffs from the area to be treated before work is commenced.

**Partial protection is provided once dry (2-4 hours) after application and full resistance to oil and water is developed over 48 hours.**

To clean surface thoroughly before treatment use HMK® R55 Intensive Cleaner -acid free-. For regular cleaning and continued protection use HMK® P24 Liquid Stone Soap, a no-rinse natural product.

Once dry the residual material is not harmful to health.

**Coverage:** About 5-20m<sup>2</sup>/litre depending on the nature of the surface.

**Warning:** Chemical product. Contains turpentine substitute. Flammable. Keep away from heat, sparks and flame. Harmful or fatal if swallowed or inhaled. Ensure the area to be treated is adequately ventilated. Avoid eye/skin contact. If exposed wash/flush with water and seek medical attention immediately. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information.

**Packaging:** 12 x 1 litre bottles/box; 4 x 5 litre cans/box; 2 x 10 litre cans/box.

**Storage:** Store in a cool place and keep lid tightly closed.

**Testing:** Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12 and above 25°C.

**Limitation of liability:** The liability of HMK® Moeller Stonecare and / or its distributors for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stonecare and / or its distributors shall not be liable for any consequential damages. No other warranty or representation is made or implied.